



Installation Guide

Reference: IG-RNG-0121

Ranger

Flexible steel edging restraint for soft landscape and aggregate pathway

Tools Required

- ✓ Hammer
- ✓ Hacksaw / angle grinder
- ✓ Level
- ✓ Tape measure
- ✓ Spray paint
- ✓ String line
- ✓ Shovel / spade

Fixings required

- ✓ 305/410mm Flat Fixing Stake
- ✓ Galvanised Connector Packs



Standard soft landscape application

1

Set out

Mark out the area you wish to install the edging into (using a spray marker or something similar) and dig a 100mm deep trench.

2

Lay the edging

Lay the edging in place ensuring the Flat Fixing Stakes are on the side of the edging that is less likely to be seen. Check vertical and horizontal level.

Fix the stakes through the loops in the back of the edging – do not fully fix down at this stage.

3

Connecting the edging

Join the edgings as shown in the image and stake down. Continue positioning and staking your edging until installation is complete.

Once you are satisfied with the layout fix the stakes down below the top of the edge.

NOTE: If you are installing into a compacted hard sub-base such as MOT Type 1 you can use 450mm steel fixing spikes to secure the edging. Please ensure that the fixing stake extends 10mm above the top of the bracket when installing.

4

Cutting / creating corners

Simply cut the edging using an angle grinder or hacksaw.

Corners can be achieved by securing the edging to a workbench or something similar and simply bending to 90 degrees. Scoring the edging using an angle grinder can assist in this.

Handling and hazards



SHARP CORNERS AND EDGES!
Wear gloves



BE SAFE!
Wear high visibility clothing, hard hats, and any other PPE required on site. We recommend 2 person handling and installation

DISCLAIMER

These instructions are for guidance only and the installer is responsible to use their discretion to install the products in the best possible way for their respective application. Kinley Systems will not be held liable for product failure or poor performance as a result of poor quality installation. If any errors are found in this guide please email us at sales@kinley.co.uk.

SUPPORTING DOCUMENTS

More information on the Ranger Edging products can be found at www.kinley.co.uk in the Resource Centre.

Want more help?

Simply contact our technical support team on **01580 830688**

Northpoint, Compass Park, Staplecross, E.Sussex TN32 5BS

e: sales@kinley.co.uk

www.kinley.co.uk